

Stainless Steel— Chemical



Premium Fittings



Insulated, Exposed Rings



Lightweight Design

MATERIAL

Available in 316L or 304L

SHELL FULL CAPACITY

4,000–40,000 liters
Built to customer specifications

WEIGHT

Built to local road regulations

Total Performance.

When it comes to moving general chemicals, food commodities, agricultural products, consumer goods and corrosive products (such as acids) efficiently and profitably, total performance during all phases of operation is paramount—from loading to transport, to unloading and cleanout and back again—with proven engineering, operator-friendly design and a leading reputation for durability.

SOLUTIONS-DRIVEN

INDUSTRY LEADERSHIP

ENDURING PERFORMANCE

Stainless Steel— Chemical



WWW.HEILASIA.COM

BARREL SHAPE	Straight round or double taper with external rings
CONSTRUCTION MATERIAL	Available in 316L and 304L
SERVICE CLASSIFICATION	Available in standard, heavy, super and extreme-duty ratings
SHELL FULL CAPACITY	From 5,000 to 40,000 liters
TEMPERATURE	-20° C to 140° C
CODE	Code or non-code
BAFFLES	None
INTERNAL WELD FINISH	W-0 through W-5
PASSIVATION	The complete interior of the tank will be passivated via a wash process
EXTERNAL WELD FINISH	W-0 through W-5
VENT	25 psi, 30 psi and 35 psi available. Atmospheric available for non-code
PRESSURE PACKAGE	Available option to include 1" SS ball valve and pressure gauge (0-60 psi)
VAPOR RECOVERY	Provisions for VR
CLEANOUTS	3" Stainless steel with SS cap
EMERGENCY VALVE	316 Stainless steel external, hydraulic valve
PIPING AND VALVES	Piped to meet customers' specifications
MANHOLE	20" Stainless full opening with eyebolt and wingnut hold-downs located at center of tank
SPILL DAM	Code-compliant stainless steel rollover protection/spill dam, located at approximately center of trailer

PRESSURE UNLOAD	Available option
LADDER	Stainless steel or aluminum, mounted to walkway, bolted top and bottom
WALKWAY	Optional: platform mounted on stainless steel brackets, ladder side, at spill dam. Extended walkways available
FENDERS	Aluminum fenders with Heil Trailer anti-sail/anti-spray mudflaps at rear
CABINET	Customer specified
TIRE CARRIER	Customer specified
HOSE CARRIER	Tube or trays available
LANDING LEGS	Gear type, 2-speed, sealed gearbox with shoes and crank
SUBFRAME	High-tensile steel subframe
BUMPER	Steel, available full width or split center
UNDERRIDE	Steel
SUSPENSION	Air-ride or mechanical suspension
WHEEL END	OEM supplied
BRAKE SYSTEM	4S/2M ABS with EBS option
PAINT	Steel parts will be painted black enamel
WIRING	In conduit
LIGHTING	LED 24-volt system or multi-volt available
DECALS	Customer specified
PRODUCT PUMP	Customer specified

Warranty and Support

Strong tradition
of aftermarket parts
and service.

Standard warranty,
backed with a team of highly
experienced engineers.

Reputation for best-in-class
manufacturing and design
of tank trailers.



Heil Trailer is part of the Engineered Transportation International family of brands.

Follow us @HeilAsia   

Heil Trailer Asia Limited • Bang Pa-In Industrial Estate, 168 Moo 16 Udomsorayut Rd. • Bang Grasan, Bang Pa-In, Ayutthaya, 13160, Thailand
+66(0)352 21 000 • inquiries@heilasia.com • www.heilasia.com

Copyright © 2024 Heil Trailer International, Co. USA. All Rights Reserved.